



DeLorean Motor Company Lighted Key

Assembly Instructions

Thank you for purchasing a **DeLorean Motor Company Lighted Key**. The following instructions are included to insure that you have no problems assembling the key. If, however, you have any problems, do not hesitate to call us for assistance. **Read the instructions through completely prior to beginning the assembly procedure!**

Tools/parts required:

106244 - Precut Key

106245 - Precut Key Internal Parts

BEREC RM625N battery or equivalent (not included)

Separate all the pieces supplied into your work area as shown in the photo below:



A
Cover

B
Button

C
Battery

D
Actuator

E
Spring

F
Bulb/Contact

G
Key

Insert part "F" into the hole on the key itself "G", so that the contact lays flat in the key. Place the spring on top of the contact, with the narrow end of the spring pointing up. Insert the actuator "D" in the key so that the lip on the long end of the actuator is pointing up and laying against the bottom of the bulb. The round hole in the actuator will fit on a peg in the key "G".

The positive terminal side of the battery should fit snugly in the plastic button "B", which then is fitted into the large black cover "A". Holding the button and battery in place in the cover "A", align the pegs on the cover with the holes in the key "G" and press together firmly. The bulb should illuminate only when the button is pressed.

Disassembly when you need to replace the battery is accomplished by carefully inserting a screwdriver into the indented slot at the top of the key and gently separating the cover from the key, exercising care so the spring and internal pieces are not lost.